

DVR- F1104

4CH/1 SATA DVR




KEY FEATURES

- 1 SATA (Maximum support 6T B)
- Support AHD / TVI 720P / 1080P
- Support VGA, HDMI 1080N HD output
- Video Compression H.264 High Profile
- 4Ch Audio Input/ 1 Ch Audio Output

DVR- F1104 4CH/1 SATA DVR

DIMENSION



INTERFACE



SPECIFICATION

VIDEO

| | |
|---------------------------|-------------------------------|
| Video Compression | H.264 High Profile |
| Encode Ability | 4ch*1080N@15fps |
| Decode Ability | 4ch *1080N@15fps |
| Video Input (Pure Analog) | 4ch*720P |
| | Support 4ch*1080P |
| Mixed: | 2ch*AHD(720P)+2ch*TVI(720P) |
| | 2ch*AHD(1080P)+2ch*IPC(720P) |
| Support | 2ch*AHD(1080P)+2ch*TVI(1080P) |
| | 2ch*AHD(1080P)+2ch*IPC(1080P) |
| Pure Network | 4ch*720P |
| | Support 4ch*1080P |

AUDIO

| | |
|-------------------|---------|
| Audio Compression | G.711A |
| Two Way Audio | Support |

RECORD AND PLAYBACK

| | |
|------------|------------------------------|
| Hard Drive | 1 SATA (Maximum support 6TB) |
| Record | Manual/Event/Timer |
| Playback | 4ch(pure local input mode) |

STORAGE & BACK UP

| | |
|------------------|---------------------------|
| Space Occupation | 960H:12~20G/ day*channel |
| | 720P:~20G/ day*channel |
| | 1080P 20~30G/ day*channel |
| | Audio:691.2M/ day*channel |
| Backup Mode | USB HDD |

INTERFACE

| | |
|-------------------|--|
| Video Input | 4ch BNC (AHD/TVI/CVBS) |
| Video Output | 1ch VGA,1ch HDMI |
| Audio Input | 4ch RCA |
| Audio Output | 1ch RCA |
| Network Interface | 1 RJ45 10M/100M Adaptive Ethernet Port |
| PTZ Control | RS485, Support Multiple PTZ Protocols |
| USB | 2 USB |

GENERAL

| | |
|-----------------------|-------------------------------|
| Power | DC12V/2A |
| Operating Temperature | -10°C ~ 50°C (14°F ~ 122°F) |
| Dimension | 255mm(L) x 255mm(W) x 45mm(H) |