

Phaser 3435D/3435DN Black & White Laser Printer High-end features, priced right for your business



Serious performance when quality and productivity count.

Superb output, **low cost and reliable**. The versatile Phaser 3435 black and white laser printer offers big-business features such as built-in networking*, automatic two-sided printing and expansion options. For busy offices and workgroups, the choice is clear.

* Phaser 3435DN only



Affordable, powerful business printer

The Phaser 3435 keeps your office or workgroup functioning at peak performance. Available in network and non-network configurations, this efficient printer delivers impressive, business class documents.

- 33 pages-per-minute(ppm) speeds up printing of multiple A4-size documents.
- 1200 x 1200 dpi output produces sharp text and graphics.
- **8.5-second** first-page-out-time reduces waiting time between print jobs.
- Automatic two-sided printing generates professional looking reports and saves paper.
- 400 MHz processor and standard 64 MB memory handle complex documents without delay.
- 80,000-page maximum monthly duty cycle meets the requirements of unusually high print demands.







More features for peak productivity

1 50-sheet multipurpose tray accepts envelopes, labels and other thick media as well as custom sizes from 76 x127 mm to 215.9 x 356 mm.



- 2 250-sheet paper cassette is adjustable to take a variety of sizes, including A4, Letter, Legal, A5 and B5.
- 3 Optional 250-sheet paper cassette installs easily and increases total media input capacity to 550 sheets.





4 Intuitive, two-line LCD control panel for easy access to the printer menu.



Automatic two-sided printing at 17 impressions-per-minute is ideal for printing reports and saves paper.

64 MB RAM handles complex documents with graphics efficiently.

10/100Base-TX interface* for workgroup printing.

Centreware Internet Services (IS)* shows printer status information and allows configuration of settings via a web browser.

* Phaser 3435DN only

Quality output

Featuring 1200 dpi print resolution, the Phaser 3435 reproduces small text, fine lines and detailed graphics beautifully. Support for Postscript 3 smoothes gradations in graphics such as illustrations and photos.

Built for speed

Fast 33 ppm printing increases office efficiency, especially when printing multi-page documents. In addition, an 8.5-second first-page-out-time and 15-second warm-up time further enhance speed and productivity.

Workgroup friendly*

Add the Phaser 3435 to your workgroup for outstanding productivity. Built-in 10/100Base-TX networking and multi-platform support — including Windows, Mac and Linux — making it perfect for nearly any office.

* Phaser 3435DN only



Specifications of Phaser 3435D / Phaser 3435DN

Print Functions

| Print Functions | | | |
|--------------------------|--|---|--|
| | Phaser 3435D | Phaser 3435DN | |
| Print Speed | Simplex: Up to 35 ppm (Letter), 33 ppm (A4) | | |
| | Duplex: Up to 17.5 ipm (Letter), 17 ipm (A4) | | |
| Print Resolution | Up to 1200 x 1200 dpi effective output | | |
| First-Page-Out-Time | As fast as 8.5 seconds | | |
| Warm-up Time | Less than 15 seconds | | |
| Memory (std/max) | 64 MB Flash ROM (includes 4 MB for additional fonts and macros) / 320 MB | | |
| Processor | 400 MHz | | |
| Printer Language | PCL6, PostScript® 3™, IBM ProPrinter, EPSON | | |
| Connectivity | USB 2.0, Parallel | Ethernet 10/100Base-TX, USB 2.0, Parallel | |
| Operating System | Windows® 2000/ XP (32/64 bit)/ Vista® (32/64 bit)/Server® 2003 (32/64 bit), Linux® (Ubuntu, Red Hat® 8-9, Fedora Cores 1-4, Mandrake 9.2-10.1, SuSE® 8.2 - 9.2), Mac OS X 10.3-10.5 | | |
| Input Paper Size | Tray 1 and Tray 2 (optional): Plain Paper -A4, A5, Letter, Legal, Executive, Folio, ISO B5, JIS B5 Multipurpose Tray: Plain Paper - A4, A5, Letter, Legal, Executive, Folio, ISO B5, JIS B5, 3" x 5"; Envelopes - Monarch, No.9, No. 10, DL, C5, C6; Cardstock; Custom size - 76 x 127 mm - 215.9 x 356 mm Duplex: Plain Paper -A4, Letter, Legal, Folio, Officio | | |
| Input Paper Weight | Tray 1 and Tray 2 (optional): 60 - 90gsm Multipurpose Tray: Plain Paper 60 - 90gsm; Others 60 - 163gsm Duplex: 75 - 90gsm | | |
| Media Input Capacity | Standard: Multipurpose Tray: 50 sheets, Tray 1: 250 sheets Optional: Tray 2: 250 sheets | | |
| Media Output Capacity | 150 sheets face down | | |
| Dimensions (W x D x H) | 400 x 435 x 314 mm | | |
| Weight | 12.7 kg | | |
| Power Supply | 220 – 240 VAC, 50/60 Hz | | |
| Power Consumption | Average: 400W; Power save mode: Less than 11W | | |
| Operating Environment | Temperature: 10 °C - 32 °C Humidity: 20 - 80% RH | | |
| Noise Levels | Standby mode: Less than 25dBA; Printing mode: Less than 54dBA | | |
| Device Management | _ | Phaser Installer, CentreWare® IS Embedded Web Server, CentreWare Web, Global Print Driver | |
| Warranty | Please check with your Fuji Xerox Printers reseller for more information. | | |

Consumables

| Print Cartridge (up to 4,000 pages*) | CWAA0762 |
|---------------------------------------|----------|
| Print Cartridge (up to 10,000 pages*) | CWAA0763 |

^{*} Average standard pages. Declared yield in accordance with ISO IEC 19752. Yield may vary depending on image, area, coverage and print mode. Printer is shipped with one starter print cartridge with an average yield of 4,000 pages.

Accessories (optional)

| 64 MB Memory EL300 128 MB Memory EL300 | 250-sheet Tray | EL300651 |
|---|----------------|----------|
| 128 MB Memory EL300 | 32 MB Memory | EL300652 |
| | 64 MB Memory | EL300653 |
| 256 MB Memory EL300 | 128 MB Memory | EL300654 |
| 3 | 256 MB Memory | EL300655 |









Descriptions in this material, product specifications and/or appearances are subject to change without prior notice due to improvements. Please note that the product colour appears differently from the actual colour as a result of properties of papers or printing ink. Windows and Windows NT are registered trademarks of Microsoft Corporation. NetWare is a registered trademark of Novell, Inc. in the United States. Macintosh, Mac OS and Ether Talk are trademarks of Apple Computer, Inc. PostScript is a registered trademark of Adobe Systems Incorporated in each country, HP-GL is a registered trademark of Hewlett Packard Company. Bulklinks is a trademark of the Japan Business Machine and Information System Industries Association (JBMIA). Other company names or product names are registered trademarks or trademarks of each company.

<Reproduction Prohibitions> Please note that reproduction of the following is prohibited by law:
Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates. Unused postage stamps and post cards. Certificate stamps stipulated by law. The reproduction of works for copyright purposes (literary works, musical works, paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range according to the above. This product is equipped with an anti-counterfeit feature. This feature is not intended to prevent illegal reproduction. Be extremely careful about the management of equipment used



For Your Safe Use
Before using the product, read the Instruction Manual carefully for proper use.
Use the product with an appropriate adequate power source and voltage displayed. Be sure to establish a ground.
In the case of a failure or short circuit, an electric shock may result.



For more information or detailed product specifications, please call or email or visit our website at:

Fuji Xerox Asia Pacific Pte Ltd

80 Anson Road #36-00

Fuji Xerox Towers Singapore 079907

Tel: +65 6351 0118 Email: sgp.sales@fujixerox.com

http://www.fxprinters.com.sg