

Specifications

Print Function	Model	DocuPrint P205 b	DocuPrint M205 b	DocuPrint M205 f / fw
Print Speed (A4/letter)			Up to 24 ppm	
Print Resolution			1200 x 1200 dpi	
First-page-out Time			11 seconds or less	
Warm-up Time		25 seconds or less		36 seconds or less
Memory (std/max)		64MB		128MB
Processor		150 MHz		300MHz
PDL			Host-based	
Connectivity		Hi-speed USB 2.0		10/100BaseT, Hi-speed USB 2.0
Wireless Function		Available on DocuPrint M205 fw		
Compliant Standard		--	--	IEEE802.11b/g
Security Protocol		--	--	WEP (64/128bits), WPA-PSK (TKIP, AES), WPA-2PSK (AES)
Certifications		--	--	Wifi, WPA2.0 (Personal)
Wifi Protected Setup (WPS)		--	--	Push Button Configuration (PBC), Personal Identification Number (PIN)
Supported Operating System		Windows XP (32bit/64bit), Server 2003 (32 bit/ 64bit), Vista (32bit/64bit), Server 2008 (32bit/64bit), Server 2008R2 (64bit), 7 (32bit/64bit) Mac OS Version 10.4.11 or later (Power PC 32bit/Intel 32bit), 10.5 with the latest update (Power PC 32/64bit/Intel 32/64bit) and 10.6 with the latest update (Intel 32bit/64bit)		
Input Paper Size Main Tray		A4 SEF, B5 SEF, A5 SEF, Letter SEF, Executive SEF, Folio (8.5" x 13") SEF, Legal SEF, Statement SEF, Envelope (Com-10 SEF, Monarch SEF/LEF, DL SEF/LEF, C5 SEF), Postcard SEF, W-Postcard SEF	Custom size width 76.2 to 215.9mm Length 127 to 355.6mm	Custom size width 76.2 to 215.9mm Length 148 to 355.6mm 150 + 10 sheets
Media Input Capacity		150 sheets		
Media Output Capacity			100 sheets face-down	
Media Types Main Tray			Plain, Recycled, Labels, Covers, Envelope, Postcard	
Input Paper Weight Main Tray			60 - 163gsm	
Monthly Duty Cycle			Up to 20,000 pages/month	
Engine Life			30,000 pages or 5 years	
Print Features		Toner Save Mode, Manual Duplex, Print Cancel (from panel), N-up, Poster, Watermarks, Collate, Image Rotation (180degree) Direct USB Print (TIFF/JPEG/PDF)**		
Dimensions (WxDxH)		358 x 197 x 208mm	410 x 389 x 299mm	410 x 389 x 318mm
Weight		4.6kg	8.9kg	9.9kg
Operating Environment Temperature		Storage: -20° to 40° C, Operating: 10° to 32° C		
Humidity		Operating Environment: 10% to 85% RH		
Sound pressure levels		Standby: 15dB(A), Printing: 52dB(A)	Standby: 15dB(A), Printing: 54dB(A)	
Electrical Power		220-240 VAC, 50/60 Hz		
Power consumption		Standby: 62W, Printing: 380W Power save: 4.0W; ENERGY STAR® qualified	Standby: 58W, Printing: 380W Power save: 3.5W; ENERGY STAR® qualified	Standby: 58W, Printing: 400W Power save: 3.5W; ENERGY STAR® qualified
Copy Function				
Copy Speed		--	Up to 24 cpm	
Copy Resolution		--	Up to 600 x 600 dpi	
First-copy-out Time		--	24 seconds or less	
Reduction / Enlargement		--	25 - 400%	
Continuous Copy		--	1 - 99 pages	
Copy Feature		--	ID Card Copy, 2 in 1 Copy, Edge Erase, Collate (Electronic Sort)	
Scan Function				
Type Colour		--	Colour CIS	
Scanning Resolution		--	1200 x 1200 dpi (optical); up to 4800 x 4800 dpi (enhanced)	
Colour Depth		--	24 bit	
Document Size		--	Flatbed: 215.9 x 297 mm	Flatbed: 215.9 x 297 mm ADF: 215.9 x 355.6 mm
Scan Destinations		--	Direct Scan to USB Memory Drive, Scan to Application (PDF/JPEG/TIFF)	Scan to Email, Scan to FTP, Scan to SMB (PDF/JPEG/TIFF)
Supported Driver		--	TWAIN, WIA	
Bundled Software		--	Docuworks 7.2	
Fax Function				
Compatibility		--	ITU-T G3	
Communication System		--	PSTN, PBX (PABX)	
Transmission Speed		--	Up to 33.6 kbps	
Memory Capacity (MB)		--	2MB	
Fax Resolution		--	400 x 400dpi (Max)	
One-Touch/Speed Dials		--	Up to 8 locations / Up to 99 locations	
Fax Features		--	PC Direct FAX, Secure FAX Receive, Remote Fax Receive, Junk FAX Filter	
Warranty		One-to-One Swap (return to depot)***		One-to-One Swap (on-site)***
Consumables				
Standard yield toner cartridge (up to 1,000 pages*)		CT201609		
High yield toner cartridge (up to 2,200 pages*)		CT201610		

* Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode. Printer is shipped with one standard toner yield 1,000 pages.
** Refers to JPEG / TIFF (single TIFF without LZW / PDF (ver 1.3 image) only).
*** Terms and conditions apply. Please refer to FujiXerox Printer's website for more details.

Descriptions in this material, product specifications and/or appearances are subject to change without prior notice due to improvements. Please note that the product colour appears differently from the actual colour as a result of properties of papers or printing ink. Windows is a registered trademarks of Microsoft Corporation. Macintosh, Mac OS and Ether Talk are trademarks of Apple Computer, Inc. Other company names or product names are registered trademarks or trademarks of each company.



Reproduction Prohibitions Please note that reproduction of the following is prohibited by law. Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates. Unused postage stamps and post cards. Certificate stamps stipulated by law. The reproduction of works for copyright purposes (literary works, musical works, paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range according to the above. This product is equipped with an anti-counterfeit feature. This feature is not intended to prevent illegal reproduction. Be extremely careful about the management of equipment used.



For Your Safe Use

Before using the product, read the Instruction Manual carefully for proper use.
Use the product with an appropriate adequate power source and voltage displayed.
Be sure to establish a ground.
In the case of a failure or short circuit, an electric shock may result.

For more information or detailed product specifications, please call or email or visit our website at:

Fuji Xerox Asia Pacific Pte.Ltd. (993478-A)
(Fuji Xerox Printers)
Wisma Fuji Xerox, 1st Floor, No. 10, Jalan Bersatu 13/4,
46200 Petaling Jaya, Selangor, Malaysia.
Tel: 03-7882 2888 Fax: 03-7882 2767

East Malaysia Office:
199A-201, Lot 3049 & 3050, Eastmoore Centre,
2½ Mile, Jalan Rock, 93200 Kuching,
Sarawak, Malaysia.
Tel: 082-428 650 Fax: 082-418 733

FUJI XEROX

Service Hotline : 1800 88 1063
www.fujixeroxprinters.com.my

XEROX, and the sphere of connectivity design are trademarks or registered trademarks of Xerox Corporation in the U.S. and/or other countries. AperaPort is a trademark or registered trademark of Fuji Xerox Co. Ltd. Other trademarks are the property of their respective owners.

DocuPrint

P205 b / M205 b
M205 f / M205 fw

FUJI XEROX

DocuPrint P205 b / M205 b DocuPrint M205 f / M205 fw Monochrome LED Printer

Small effort, big results

