

Features

High Compatibility and Innovative Design

WFT510 is the ONLY wireless foto transmitter designed to work with PictBridge compatible digital cameras*, including high-end DSLR and consumer-type cameras.



* Actual compatibility may vary by cameras.

Wireless Transmission

Allow users to transmit images from a PictBridge compatible digital camera to a photo printer with wireless function.



Affordable Wireless Foto Transmitter

WFT510 comes at an affordable price, allowing consumers to enjoy wireless transmission function just like the high-end DSLR cameras users.

Easy Operation*

With switch button design, WFT510 is able to activate PictBridge mode of digital camera easily. After shooting a photo, user will only need to click the switch button, select photos, and then transmit photos to printer or PC wirelessly.



* The operation process may be slightly different depends on what digital camera is used.

PC connectivity

By installing WFT PC Kit, bundled with WFT510, users can transmit image data directly to computer, which further enhances the flexibility of wireless transmission solution.



Auto Setting Function

WFT PC Kit provides AUTO setting function, assisting users to set up their PCs to receive the images through WFT510 easily.



Specification

Item	Description
Hardware	
Wireless Standards	IEEE 802.11b/g Compatible
Transmission Method	IEEE 802.11b: DQPSK, DBPSK
	IEEE 802.11g: OFDM
Transmission Frequency	2,412MHz-2,472 MHz
Antenna	Gain 2 dBi
Transmission Range	Approximately 100m
	(With no obstructions between the transmitter and
	receiving device and no radio interference)
Data Rates	1-11 Mbps for IEEE 802.11b,
	6-54 Mbps for IEEE 802.11g
	(Logical data rates according to IEEE standard.
	Actual rates may vary by operation environment.)
Connection Method	Ad-hoc/Infrastructure
Camera Connection	USB2.0 Hi-Speed
PC/Printer Connection	USB 1.1 (Micro USB)
Camera Connection Protocol	PictBridge
Network Protocol	TCP/IP, FTP
Power Consumption	4W Maximum
Power source	4 rechargeable or alkaline AA batteries
Operation Condition	Temperature: 0°C ~40°C /35°F~103°F
	Humidity: less than 85% (no condensation)
Dimension (W*H*D)	68mm x 140mm x 30mm
Weight	Approximately 155g (body only)
Software	
Software Name	HiTi WFT PC Kit
Operation System	Windows XP / Vista
Connection Method	Ad-hoc /Infrastructure

TCP/IP. FTP




PC Connection

Network Protocols



WFT510 Carry Bag and Hook



· Fasten by belt

North America HiTi Digital America, Inc.

727 Brea Canyon Rd. Suite#2 Walnut, CA 91789, USA

Tel: +1-909-594-0099 Fax: +1-909-598-0011

Latin America

HiTi Digital, Inc. (Mexico)

Agustín Gonzalez de Cossio No. 1-202 Col. Del Valle, C.P. 03100, Mexico, D. F. Mexico

TEL: +52-55-50253671, +52-55-50253672

Middle East · Africa

HiTi Digital, Inc. MEA

Office No. 1608, Indigo Icon Tower, JLT, Dubai - U.A.E. Tel: +971-4-3674547 Fax: +971-4-3674221 www hiti com

HiTi Digital, Inc.

HiTi Digital, Inc. (New Delhi Liaison Office)

Tel: +91-11-4180-8191

Fax: +91-11-4180-8193 www.hiti.com

401/402, 4th floor, 96, Siddharth Building Nehru Place, New Delhi 110019

- ▲ © 2010 HiTi Digital, Inc. All Rights Reserved.
- ▲ PictBridge is a trademark. All other trade names and trademarks are property of their respective owners
- ▲ Specifications are subject to change without prior notice.

P/N:70.00DWT.E12

Taiwan (Headquarters)

HiTi Digital, Inc.

9F, No. 225, Sec. 3, Beixin Rd., Xindian City, Taipei County 231, Taiwan Tel: +886-2-2912-6268
Fax: +886-2-2912-6118
www.hiti.com

Service & Support Centers

China

HiTi Digital Suzhou, Inc.

No.58, XinQing Road, Suzhou Industrial Park, JiangSu, China Tel: +86-512-8717-1688

Fax: +86-512-6760-1186 www.hiti.com/cn

Europe · Russia

HiTi Digital Europe B.V.

ESP 206, 5633 AC, Eindhoven, The Netherlands Tel: +31-40-2565166

Fax: +31-40-2903176 & +31-40-2903287 www.hiti.com