



Synology DiskStation DS212

Feature-rich 2-bay NAS Server for Workgroups and Offices

Synology® DiskStation DS212 offers an affordable and full-featured network attached storage solution, specifically designed for small business workgroup users who need to share and protect data cost-effectively, while increasing productivity with comprehensive business-oriented applications. Running on DiskStation Manager (DSM) operating system, it delivers ease of use and variety of features.

Highlights

- Optimal Price/Performance Ratio
- Features SuperSpeed USB 3.0
- Hardware Encryption Engine
- Cool and Quiet Design
- Effective Backup Solutions
- Running on Synology DiskStation Manager (DSM)

Optimal Price/Performance Ratio

Synology DS212 delivers an average 110 MB/sec reading speed under RAID 1 configuration in a Windows environment, and 54.3 MB/sec writing. DiskStation DS212 provides a reliable solution for data sharing with an easy to use interface, and comprehensive office applications, including a complete backup solution making it one of the best values in 2-bay NAS devices available today.

Coming with USB 3.0 support which offers transmission speeds of up to 5 Gbps, namely 10 times faster than USB 2.0, DS212 takes less time for data transfer for external hard drives and consumes less power. In addition, hot-swappable drives make it easier for maintenance and hard drive replacement.

Simple Sharing

Synology DS212 offers comprehensive network protocol support, assuring seamless file sharing across Windows, Mac, and Linux platforms. Windows ADS and LDAP integration allows the Synology DS212 to quickly and easily fit into an existing business network environment with no need to recreate user accounts on the Synology DS212. Internet file access is simplified by the encrypted FTP server and the web-based File Browser. HTTPS, the built-in firewall, and IP auto-block support ensure file sharing over the Internet is protected at a high security level.

If you are always on the move, Synology provides a handy app, DS file for iPhone, iPad and Android users. Anything stored on Synology DS212 can now be accessed remotely using DS file via the Internet.

Business Applications

Synology DS212 runs on the award-winning operating system, Synology DiskStation Manager (DSM), offering comprehensive applications and features designed specifically for home and business workgroups.

The built-in mail server turns Synology DS212 into a dedicated mail service provider, and the USB printer sharing capability minimizes businesses' cost by sharing printing resources throughout the office. VPN Server package offers an easy VPN solution that turns your DS212 into a VPN server, providing a secure way of connecting to a private LAN at a remote location.

Synology Web Station with support for PHP/MySQL web content allows hosting of up to 30 websites, and 3rd party web applications such as Content Management, Customer Relationship Management & e-Commerce system.

Effective Backup Solutions

Synology DS212 offers a centralized backup target to consolidate fragmented and unstructured data across a network. PC users can back up their data to Synology DS212 using Synology Data Replicator software, and Mac OS X users enjoy native Apple® Time Machine integration.

A backup wizard is provided for backing up data from Synology DS212 to another Synology DiskStation, to other rsync server, or to an external drive. Backing up to Amazon® S3 cloud service is also supported. The add-on package, Time Backup, keeps DiskStation data in multiple versions, so IT administrators could easily keep track of them and restore to a previous version whenever required.

USBCopy and SDCopy provide a plug-n-save solution to store data. By pushing the «Copy» button on the front panel, you can quickly back up all data from your USB storage device or SD card to your DiskStation.

Peace of Mind with Data Encryption

The Synology DS212 is equipped with an encryption engine which offloads the encryption calculation task away from the main CPU, helping to improve file transfer speeds of the DiskStation.

Data protection is an important matter for businesses of all sizes. High-end features previously available only on enterprise level hardware are now accessible via Synology DS212 to small and medium-sized businesses. DS212 provides share-level AES 256-bit encryption to aid in the prevention of unauthorized access attempts to the hard drives.

Energy Efficient with Cool and Quiet Design

Synology DS212 is designed with energy efficiency in mind. Not only does it provide a 92x92 mm fan and the smart airflow to keep the system running cool 24/7, its noise dampening design makes it really quiet compared to PC counterparts. The support of Wake on LAN/WAN, multiple scheduled power on/off, and hard drive hibernation can further reduce power consumption and operation cost.

All Synology products are produced with RoHS compliant parts and packed with recyclable packaging materials. Synology acknowledges the responsibility as a global citizen to continually work to reduce the environmental impact of every product produced.

CONNECTIONS & BUTTONS





SYNOLOGY INC.

Founded in 2000, Synology is a young and energetic company dedicated to developing high-performance, reliable, versatile, and environmentally-friendly Network Attached Storage (NAS) products. Our goal is to deliver user-friendly solutions and solid customer service to satisfy the needs of businesses, home offices, individual users and families.

Copyright © 2011, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or ayriology, the syniology logo are trademists of registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice Printed in Taiwan, DS212-2011-ENU-REV004

http://www.synology.com

Headquarters

Synology Inc. 3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

North & South America

Synology America Corp. 2899 152nd Ave NE, Redmond, WA 98052. USA Tel: +1 425 818 1587

Synology UK Ltd. Davy Avenue, Knowlhill, Milton Keynes, Bucks,

MK5 8PB, UK Tel: +44 01908 673 709

Technical Specifications

Hardware

- CPU Frequency: 1.6GHz
- Memory: 256MB

- Memory: 256MB Internal HDD: 2X.5." SATA(II) or 2X 2.5" SATA/SSD Max Internal Logacity: 6TB (2X 3TB hard drives) (hard drives not included) Hot swappable HDD Size (H54WD: 165mm X 108mm X 233.2mm External Storage Interface: USB 3.0 X 2, USB 2.0 x 1, SD card slox Y 3. slot X 1
- · Wake On LAN
- Wake On LAN
 Weight: 1.25Kg
 LAN: Gigabit X1
 Wireless Support (wireless dongles not included)
 Hardware Encryption Engine
 Fan: X1(92 X 92mm)
 Power Recovery
 AC Input Power Voltage: 100V to 240V
 Power Frequency: 50Hz to 60Hz, Single Phase

- · Power Consumption1: 18.2W (Access); 6.8W (HDD Hibernation)
- Power Consumption: 16.24w (Access); 6.38w (Ind.)
 Operating Temperature: 5°C to 35°C (40°F to 95°F)
 Storage Temperature: -10°C to 70°C (15°F to 155°F)
 Relative Humidity: 5% to 95%RH
 Maximum Operating Altitude: 10,000 feet
 Certification: FCC Class B, CE Class B, BSMI Class B

Applications

File Browser • Virtual Drive

· Remote Folde

- FTP Server

 Bandwidth Control

 Custom FTP Passive Port Range
- Anonymous FTP
 Transfer Log

Mail Server

Supported Mail Server Protocol : POP3, SMTP, IMAP

Web Station

- Virtual Host (up to 30 websites)
- PHP/MySQL
 Alternative HTTP Error Page
 3rd-Party Applications Support

Surveillance Station

Default IP cam #: 1

MAX IP cam # (licenses required): 8 (1 free license to install 1

IP camera. Additional licenses can be purchased to expand the license quota.)

Photo Station

- Facebook Integration
- Facebook Integration
 Supported Image Format: BMP, JPG (jpe, jpeg), GIF, RAW (arw, srf, sr2, dcr, k25, kdc, cr2, crw, nef, mrw, ptx, pef, raf, 3fr, erf, mef, mos, orf, rw2, dng, x3f)
 Supported Video Format: 3G2, 3GP, ASF, AVI, DAT, DivX, FLV, M4V, MOV, MP4, MPEG, MPG, QT, WMV, XviD, RM, RMVB, VOB,

RV30, RV40, AC3, AMR, WMA3 (User can click and download the following video formats: RM, RMVB, VOB, RV30, RV40, AC3, AMR, WMA3, but not able to play it in Photo Station as compressed Flash video.)

Download Station

- Supported Download Protocols: BT/HTTP/FTP/NZB/eMule
 Custom BT Port
 BT / eMule Bandwidth Control

- Audio Station

 Supported Audio Format: (USB Mode) AAC, FLAC, M4A, MP3, Ogg Vorbis, WMA, WMA VBR; (Streaming Mode) MP3, M4A, M4B

 Supported Playlist Format: M3U, WPL

 Internet Radio: SHOUTcast, Radioio

DLNA/UPnP Media Server

- DLNA/UPnP media servei
 PS3/Xbox 360 Support
 Supported Audio Format: AAC, FLAC, M4A, MP3, Ogg, Vorbis,
 PCM, WAV, WMA, WMA VBR, WMA PRO, WMA Lossless
 Supported Video Format: 3GP, 3G2, ASF, AVI, DAT, DixX, DVR-MS, ISO, M2T, M2TS, MAY, MXV, MP4, MP6G1, MP6G2, MPF6A,
 MTS, MOV, QT, SWF, TF TRP, TS, VOB, WMV, XwID, RV30, RV40,
- wits, mov, ct.; swr; it; ite; 1s, vos, wmw, xvio, nvsu, nvsu, ACS, AMR, WMAS, RMVB Supported Image Format: BMP, JPG (jpe, jpeg), GIF, ICO, PNG, PSD, TIF (tiff), UFO, RAW (arw, srf, sr2, dcr, k25, kdc, cr2, crw, nef, mrw, ptx, pef, raf, 3fr, erf, mef, mos, orf, rv2, dng, x3f)

iTunes Server
- Supported Audio Format: MP3, M4A, M4P, WAV, AIF (The music

in WAV and AIF format can be streamed, but the metadata (ex:

- title, album) may not be indexed on the iTunes.) Supported Video Format: M4V, MOV, MP4
- Supported Playlist Format: M3U, WPL

Print Server

- Moak Timeter #2.
 Printing Protocols: LPR, CIFS, AppleTalk, Apple AirPrint, Google Cloud Print (For Mac users, DS212 supports PostScript USB printers only)
 Multi Functional Print Server

- Package Center

 Mail Station
 Squeezebox Server
 Webalizer
- phpMyAdmin Time Backup
- VPN Server WordPress

- Syslog Server Directory Serve HiDrive Backup

iPhone/Android Applications

DS photo+ DS audio DS cam DS file DS finder

General Specifications

Networking Protocols
CIFS, AFP, FTP, iSCSI, Telnet, SSH, NFS, SNMP, WebDAV, CalDAV

File System

- EXT4
 EXT3 (External Disk Only)
- FAT (External Disk Only)NTFS (External Disk Only)

- Volume Management
 Synology Hybrid RAID
 Max Volume #: 256

- Max Volume #: 256

 Max ISCSI Target #: 10

 Max iSCSI LUN #: 10

 Volume Type: Basic, JBOD, RAID 0, RAID 1

 RAID Migration: from Basic to RAID 1

 Expand RAID 1 with Larger Hard Drives

- Expand And F Multi-darger hand drives

 Fille Sharing Capability

 Max User Account #: 2048

 Max Group #: 256

 Max Shared Folder #: 256

 Max Concurrent Connections # (SAMBA, FTP, AFP): 128

Windows ADS Domain Integration Domain Users login via Samba/AFP/FTP/File Station

Backup Solutions Network Backup Local Backup

- Desktop Backup (using Synology Data Replicator or Apple Time Machine backup application)
- 3rd-Party Backup Support

Security

- FTP over SSL/TLS
 IP Auto-Block
- Firewall Encrypted Network Backup over Rsync
 HTTPS Connection

- Management

 DSM Upgrade

 DSM mobile

 Email Notification

 SMS Notification

 Customized User Quota

 DDNS Support
- PPPoE Resource Monitor

- UPS Management
 UPnP Router Support
 Scheduled Power On/Off
 Custom Management UI HTTP/HTTPS Ports

HDD Management HDD Hibernation S.M.A.R.T.

- Dynamic Bad Sector Mapping

Utilities Synology AssistantSynology Data Replicator

- Support Browsers
 Internet Explorer 7/8/9
- Firefox Safari 4/5 (Mac)
 Chrome

Supported Clients

Windows 2000 onward

Mac OS X 10.3 onward

Ubuntu 9.04 onward

Optional Accessories

Synology Remote Camera License Pack

IP Camera

Language

English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar, Portuguės do Brasil, Portuguės Europeu, Türkçe, Český, 日本語、한국어, 繁體中文, 简体中文

Environment and Packaging

- Environment
 RoHS Compliant
- Package Content
 DS212 Main Unit
 Installation DVD

- Welcome Note
- Assembling Kit
 AC Power Adapter
 AC Power Cord
 2M RJ-45 LAN Cable
- 1. Measured with 2 Western Digital 3TB WD30EZRS hard drives. The figures could vary on different environments

PC / Mac / Linux



PC / Mac / Linux