



Synology DiskStation DS212+

High-Performance 2-bay All-in-1 NAS Server

Synology® DiskStation DS212+ offers a high-performance, secure, and full-featured network attached storage solution that helps small and medium-sized businesses centralize backup, protect critical assets and share files quickly and efficiently. Synology protects your investment in the DS212+ with a 2-year limited warranty.

Highlights

- 109 MB/sec Reading, 56 MB/sec Writing
- Features SuperSpeed USB 3.0
- Hardware Encryption Engine
- Windows® ACL Support
- Complete Backup Solutions
- Cool and Quiet Design
- Running on Synology DiskStation Manager (DSM)

High Performance

The Synology DS212+ is designed for business users who require a reliable storage solution and demand high-performance for file sharing. The Synology DS212+ delivers an average 109 MB/sec reading and 56 MB/sec writing speeds under RAID 1 configuration in a Windows® environment.

Coming with USB 3.0 support which offers transmission speeds of up to 5 Gbps, namely 10 times faster than USB 2.0, DS212+ takes less time for data transfer for external hard drives and consumes less power. In addition, hot-swappable drives make it easier for maintenance and hard drive replacement.

Fit to Business Environment

Comprehensive network protocol support assures seamless file sharing across Windows®, Mac®, and Linux® platforms. Windows® ADS and LDAP integration allows the Synology DS212+ to quickly and easily fit in an existing business network environment with no need to recreate user accounts. Windows® ACL support provides much finer-grained access control and efficient privilege settings, allowing users to enjoy native Windows experience.

Internet file access is simplified by the encrypted FTP server and the webbased File Browser. HTTPS, the built-in firewall, and IP auto-block support ensure file sharing over the Internet is protected at a high security level.

Rich Office Applications

Synology DS212+ runs on the renowned operating system, Synology DiskStation Manager, offering applications and features designed specifically for SMBs. Directory Server package turns Synology DS212+ into an LDAP-based directory server which is capable of centralizing the management and authentication of user accounts for different applications, therefore enhancing network security and reducing management costs.

Syslog Server is an add-on package that turns your Synology DS212+ into a system log server, centralizing logs from multiple servers to your DS212+ to provide higher log preservation capability, server status transparency and help trouble shooting efficiency against multiple servers.

The built-in mail server offers a professional mail service and the USB printer sharing capability minimizes businesses' cost by sharing printing resources throughout the office. VPN Server package offers an easy VPN solution that turns your DS212+ into a VPN server, providing a secure way of connecting to a private LAN at a remote location.

Complete Backup Solutions

A backup wizard is provided for backing up data from DS212+ to another Synology DiskStation or any rsync server via an encrypted connection, or to an external hard drive via USB 3.0 or eSATA connection. The wizard also makes it easy to back up DiskStation data to the cloud via Amazon® S3. In addition, users can back up and restore DiskStation shared folders in multiple versions using Synology Time Backup package.

Shared Folder Sync allows users to synchronize a specific folder from Synology DS212+ to another DiskStation– a server-to-client backup mechanism that takes place whenever something is changed on the server side. Users will be able to share documents within their local office seamlessly and safely with encrypted connection. When your DiskStation is down, you will be able to have an immediate backup running in no time.

Peace of Mind with Data Encryption

The Synology DS212+ is equipped with an encryption engine which offloads the encryption calculation task away from the main CPU, helping to improve file transfer speeds of the DiskStation.

Data protection is an important matter for businesses of all sizes. High-end features previously available only on enterprise level hardware are now accessible via Synology DS212+ to small and medium-sized businesses. DS212+ provides share-level AES 256-bit encryption to aid in the prevention of unauthorized access attempts to the hard drives.

Energy Efficient with Cool and Quiet Design

Synology DS212+ is designed with energy efficiency in mind. Not only does it provide a 92x92 mm fan and the smart airflow to keep the system running cool 24/7, its noise dampening design makes it really quiet compared to PC counterparts. The support of Wake on LAN/WAN, multiple scheduled power on/off and hard drive hibernation can further reduce power consumption and operation cost.

All Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology acknowledges the responsibility as a global citizen to continually work to reduce the environmental impact of every product produced.

CONNECTIONS & BUTTONS





Technical Specifications

Hardware

- CPU Frequency: 2.0GHz

 Memory: 512MB
 Internal HDD: 2X 3.5" SATA(II) or 2X 2.5" SATA/SSD

 Max Internal Capacity: 6TB (2X 3TB hard drives) (hard drives not included)
 Hot swappable HDD

 Size (HxWxD): 165mm X 108mm X 233.2mm

 External Storage Interface: USB 3.0 X 2, USB 2.0 x 1, eSATA port X 1, SD card slot X 1

 For the Storage Interface: USB 3.0 X 2, USB 2.0 x 1, eSATA port X 1, SD card slot X 1
- · Wake on LAN
- Wake on LAN
 Weight: 1.25Kg
 LAN: Gigabit X1
 Wireless Support (wireless dongles not included)
 Hardware Encryption Engine
 Fan: X1(92 X 92mm)

- Power Recovery
 AC Input Power Voltage: 100V to 240V
 Power Frequency: 50Hz to 60Hz, Single Phase
- · Power Consumption1: 18.7W (Access); 7.9W (HDD

- Power Consumption: 18.7W (Access); /-JW (HUL) Hibernation)
 Operating Temperature: 5°C to 35°C (40°F to 95°F)
 Storage Temperature: -10°C to 70°C (15°F to 155°F)
 Relative Humidity: 5% to 95%RH
 Maximum Operating Altitude: 10,000 feet
 Certification: FCC Class B, CE Class B, BSMI Class B

Applications

File Browser • Virtual Drive

Remote Folder

- FTP Server

 Bandwidth Control

 Custom FTP Passive Port Range
 Anonymous FTP
 Transfer Log

Mail Server

Supported Mail Server Protocol : POP3, SMTP, IMAP

Web Station

- Virtual Host (up to 30 websites)
- PHP/MySQL
 Alternative HTTP Error Page
 3rd-Party Applications Support

Surveillance Station
Default IP cam #: 1
MAX IP cam # (licenses required): 12 (1 free license to install 1 IP camera. Additional licenses can be purchased to expand the license quota.)

Photo Station

- Facebook Integration
- Supported Image Format: BMP, JPG (jpe, jpeg), GIF, RAW
- Supported image Format: BMP, JPC (Jpe, Jpeg), Gil, KAW (arw, sft, sr2, 6r, k25, kdc, cr2, crw, nef, mrw, pbt, pef, raf, 3fr, erf, mef, mos, orf, rw2, dng, x3f) Supported Video Format 3G2, 3GP, ASF, AVI, DAT, DivX, FLV, M4V, MOV, MP4, MPEG, MPG, QT, WMV, XviD, RN, RNWP, VOB, RV3Q, RV4Q, AG2, AMR, WMA3 (User can click and download the following video formats: RM, RMVB, VOB,

RV30, RV40, AC3, AMR, WMA3, but not able to play it in Photo Station as compressed Flash video.)

Download Station

- Supported Download Protocols: BT/HTTP/FTP/NZB/eMule
- Custom BT Port
 BT / eMule Bandwidth Control

Audio Station

- Audio Station

 Supported Audio Format: (USB Mode) AAC, FLAC, MAA,
 MP3, Ogg Vorbis, WMA, WMA VBR; (Streaming Mode)
 MP3, M4A, M4B

 Supported Playlist Format: M3U, WPL
 Internet Radio: SHOUTcast, Radioio

DLNA/UPnP Media Server

- PS3/Xbox 360 Support
 Supported Audio Format: AAC, FLAC, M4A, MP3,
 Ogg, Vorbis, PCM, WAV, WMA, WMA VBR, WMA PRO, WMA Lossless
- Supported Video Format: 3GP, 3G2, ASF, AVI, DAT, DivX, DVR-MS, ISO, M2T, M2TS, M4V, MKV, MP4, MPEG1, MPEG2,
- DVR-MS, ISO, M2T, M2TS, M4V, MKV, MF4, MPEG1, MPEG2 MPEG4, MTS, MOV, CT, SWF, TF, RPT, SV, OB, WMX, XviD, RV30, RV40, AC3, AMR, WMA3, RMVB Supported Image Format BMP, JPG (jpe, jpeg), GIF, ICO, PNG, PSD, TIF (tiff), UFO, RAW (arw, srf, sr2, dcr, k25, kdc, cr2, crw, nef, mrw, ptx, pef, raf, 3fr, erf, mef, mos, orf, rv2, dng, x3f)

iTunes Server

- Supported Audio Format: MP3, M4A, M4P, WAV, AIF (The music in WAV and AIF format can be streamed, but the metadata (ex: title, album) may not be indexed on the iTunes.)

Supported Video Format: M4V, MOV, MP4
 Supported Playlist Format: M3U, WPL

Print Server

- Max Printer #: 2
- Mox Printer #: 2
 Printing Protocols: LPR, CIFS, AppleTalk, Apple AirPrint, Google Cloud Print (For Mac users, DS212+ supports PostScript USB printers only)
 Multi Functional Print Server

- Package Center

 Mail Station

 Squeezebox Server

 Webalizer

 phpMyAdmin

 Time Backup

 VPN Server

 WordPerse
- WordPress
- Syslog Server
- Directory Server
 HiDrive Backup
- iPhone/Android Applications

DS photo+ DS audio DS cam DS file DS finder

General Specifications

Networking Protocols
CIFS, AFP, FTP, iSCSI, Telnet, SSH, NFS, SNMP, WebDAV, CalDAV

File System • EXT4

- EXT4
 EXT3 (External Disk Only)
 FAT (External Disk Only)
 NTFS (External Disk Only)

- Volume Management
 Synology Hybrid RAID
 Max Volume #: 256
 Max iSCSI Target #: 10
 Max iSCSI LUN #: 10
- Max ISCSI LUN #: 10
 Volume Type: Basic, JBOD, RAID 0, RAID 1
 RAID Migration: from Basic to RAID 1
 Expand RAID 1 with Larger Hard Drives

- File Sharing Capability

 Max User Account #: 2048

 Max Group #: 256

 Max Shared Folder #: 256

 Max Concurrent Connections # (SAMBA, FTP, AFP): 256

Windows ADS Domain Integration
Domain Users login via Samba/AFP/FTP/File Station

Backup Solutions

- Backup Solutions
 Network Backup
 Local Backup
 Desktop Backup (using Synology Data Replicator or Apple
 Time Machine backup application)
 3rd-Party Backup Support

- Security
 FTP over SSL/TLS
 IP Auto-Block
- Firewall
 Encrypted Network Backup over Rsync
 HTTPS Connection
- Management
 DSM Upgrade
 DSM mobile
 Email Notification
- SMS Notification
 Customized User Quota
 DDNS Support
 PPPoE

- Resource Monitor
 UPS Management
 UPnP Router Support
- Scheduled Power On/Off Custom Management UI HTTP/HTTPS Ports

HDD Management HDD Hibernation S.M.A.R.T.

- Dynamic Bad Sector Mapping Utilities

- Synology Assistant Synology Data Replicator
- Support Browsers
 Internet Explorer 7/8/9
 Firefox
 Safari 4/5 (Mac)
- Chrome

Supported Clients

- Windows 2000 onward Mac OS X 10.3 onward
- Ubuntu 9.04 onward

Language

· English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Pycckwiñ, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český, 日本語, 한국어, 緊體中文, 简体中文

Environment and Packaging

- Environment
 RoHS Compliant
- Package Content
 DS212+ Main Unit
 Installation DVD

- Welcome Note
 Assembling Kit
 AC Power Adapter
 AC Power Cord
 2M RJ-45 LAN Cable

IP Camera

Optional Accessories
- Synology Remote
- Camera License Pack

1. Measured with 2 Western Digital 3TB WD30EZRS hard drives. The figures could vary on different environments

PC / Mac / Linux

Networking DS212+ USB Printer DS212+ Wireless Router Windows ADS Server

PC / Mac / Linux

SYNOLOGY INC.

Founded in 2000, Synology is a young and energetic company dedicated to developing high-performance, reliable, versatile, and environmentally-friendly Network Attached Storage (NAS) products. Our goal is to deliver user-friendly solutions and solid customer service to satisfy the needs of businesses, home offices, individual users and families.

Copyright © 2011, Synology Inc. All rights reserved.

Synology, the Synology logo are trademarks or ayriology, the syniology logo are trademists of registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product

descriptions at anytime, without notice.
Printed in Taiwan,
DS212+-2011-ENU-REV004

http://www.synology.com

Headquarters Synology Inc. 3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

Synology America Corp. 2899 152nd Ave NE, Redmond, WA 98052. USA Tel: +1 425 818 1587

North & South America

Synology UK Ltd. Davy Avenue, Knowlhill, Milton Keynes, Bucks, MK5 8PB, UK Tel: +44 01908 673 709